

# Decothane Accelerator

## Catalyst

**Product Description** Decothane Accelerator is designed to increase the cure rate of Decothane products to facilitate a faster application and reduce downtime in areas where a rapid return to service is required.

**Uses** An accelerator to shorten the curing time of Decothane Base Coat, Decothane Top Coat, Decothane Root Resistant Base Coat, Decothane Root Resistant Top Coat, Decothane Detail Coat, Decothane Balcons ,Decoquick and Sikalastic 625

**Characteristics / Advantages**

- Reduces downtime in areas where a fast return to service is required
- Avoids delays due to lower temperatures

## Product Data

### Form

**Appearance** Clear, low viscosity liquid

**Packaging** Available in 60ml (to be used in 5 Litre packs) and 180ml (to be used in 15 Litre packs)

### Storage

**Storage Conditions / Shelf Life** 9 months from date of production if stored properly in original, unopened and undamaged sealed pack. Expiry date on pack.

## Technical Data

**Chemical Base** Catalyst in hydrocarbon solvent

**Density** 1.02 kg/L

## System Information

## Application Conditions and Limitations

**Substrate and Ambient Temperature** Refer to the specific product technical datasheet



---

**Relative Air Humidity** Refer to the specific product technical datasheet

---

**Dew Point** Refer to the specific product technical datasheet

Beware of condensation. Surface temperature during application must be at least +3°C above dew point.

---

## Application Instructions

---

**Application Method** Mixing Level: 1% by weight.

The material should be added to the specific Decothane product on site at the time of application and mixed manually or mechanically at slow speed to prevent aeration. Mix with electric drill and paddle.

---

**Application Tools** Refer to the specific product technical datasheet

---

**Cleaning of Tools** Refer to the specific product technical datasheet

---

**Waiting Time / Overcoating** Refer to the specific product technical datasheet for the accelerated drying times.

---

## Curing Details

---

**Approximate Curing Times** Once the Decothane Accelerator is added, the specific Decothane product must be used immediately. The product has a working life of 1 hour. Ensure suitable PPE is worn when handling, mixing and applying the product.

---

## Notes on Application

---

**Health and Safety Information** For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

---

## General Information

---

**Specification Assistance** NBS is the industry standard specification system, which allows architects, specifiers and engineers to insert clauses into specifications by manufacturer and product, making the process quicker and more efficient. We are members of NBS Plus and therefore detailed up-to-date product information is readily available to create accurate specifications.

---

**Contact Details** For further information please contact:  
Sika Liquid Plastics  
Iotech House  
Miller Street  
Preston  
Lancashire  
PR1 1EA

Enquiry line: +44 (0)1772 259781  
Fax: +44 (0)1772 255670  
e-mail: [info@liquidplastics.co.uk](mailto:info@liquidplastics.co.uk)

